

Fiber Optic Accessories

Fiber Optic Adapters

FOAD-xx



Product Description

The fiber optic adapters are available in wide range of types. All standard shapes are offered in both multimode and single mode construction. The adapters include ST, SC, FC, LC and MTRJ. Also available E2000, DIN.

Features

- ▶ Comply with: JIS, IEC, Bellcore
- ▶ Precision sleeve (Zirconia & Bronze)
- ▶ Various type available
- ▶ Simplex or Duplex available
- ▶ Integrated body structure

Product Specifications

Characteristics	Values
Structure	Telecordia GR-326-CORE
Insertion Loss	< 0.2 dB (against master connector)
Mating Durability	< 0.2 dB (500 times)
Operating temperature stability	< 0.3 dB (-40°C ~ + 85 °C)

Ordering Information



Adapter 1	Polishing 2	Structure 3	Type 4	Sleeve 5	Color 6	Housing 7
SC -SC	PC - PC	SI - Simplex	SM -SM	Z -Zirconia	B -Blue	M -Metal
ST -ST	UPC - UPC	DU- Duplex	MM -MM	B - Bronze	GR -Green	P -Plastic
FC -FC	APC - APC				GY -Grey	Only for HYBRID type.
LC -LC					OT - Other	
MJ -MTRJ standard						
MJS -MTRJ with SC footprint						
D4 -D4						
DIN -DIN						
MU -MU						
E2 - LSH (E2000)						
HY -HYBRID						