

Fiber Optic Accessories

Fiber Optic Connectors

FOC-xx



Product Description

Rotal's fiber optic connectors feature a connection design that enables quick patching of cables into rack or wall mounts.

All connectors are 100% factory tested to ensure the perfect performance to meet TIA-568-B.3, ISO 11801:2002 and EN 50173-1 standards.


Features

- ▶ Comply with : IEC, Bellcore
- ▶ High stable mating and de-mating characteristics
- ▶ Optimum optical performance through high quality ferrule
- ▶ Designed for variable cable dia.
- ▶ Various connector and optical performance combinations
- ▶ Fiber compatibility: 62.5/125um and 50/125um multimode, 9/125um singlemode
- ▶ Terminable with commonly available tools
- ▶ Fast installation

Product Specifications

Characteristics	Values
Structure	Telecordia GR-326-CORE
Fiber Type	SM (9/125), MM (50/125, 62.5/125)
Insertion Loss	< 0.2 dB (against master connector)
Mating Durability	< 0.2 dB (500 times)
Operating temperature stability	< 0.3 dB (-40°C ~ + 85 °C)

Ordering Information



Connector 1	Polishing 2	Mode type 3	Boot Size 4
SC -SC	P -PC	SM - Single Mode	9: 0.9mm
ST -ST	U -UPC	MM - Multi Mode	2: 2.0mm
FC -FC	A -APC		3: 3.0mm
LC -LC			4: 0.9mm & 3mm
MJ -MTRJ			
MJM -MTRJ Male			
SMA -SMA			
MPO -MPO			
E2 - LSH (E2000)			
ES -ESCON			
DIN -DIN			
MU -MU			
D4 -D4			